


### Specifications 规格

Nominal Voltage 额定电压	12V	
Rated Capacity(20 hour rate) 20小时率额定容量	0.7AH	
尺寸 Dimensions ±1mm	Length 长	96mm(3.77")
	Width 宽	25mm(0.98")
	Height 高	55mm(2.17")
	Total Height (with terminals) 总高含端子	
Weight 重量	Approx.0.35kg (0.77lbs)	
Standard Terminal 标准端子	P1	

### 放电特性 Discharge Characteristics(20°C,68°F)



### Electrical Specifications 电性能

容量 Capacity 77°F(25°C)	20 hour rate (35mA) 20小时率	0.7AH
	10 hour rate (70mA) 10小时率	0.7AH
	5 hour rate (120mA) 5小时率	0.6AH
	1 hour rate (400mA) 1小时率	0.4AH
Internal Resistance 内阻	Fully charged battery 充足电 77°F(25°C)	110mΩ
Capacity 温度 Affected by 对容量 Temperature 影响 (20 hour rate) 20小时率	104°F(40°C)	102%
	77°F(25°C)	100%
	32°F(0°C)	85%
	5°F(-15°C)	65%
自放电 Self-Discharge 77°F(25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
Charge 充电 Constant (恒压) Voltage	循环使用: 首次充电电流低于0.21A 电压: 14.4-15.0V77°F(25°C) 浮充使用: 电压13.5-13.8V77°F(25°C) Cycle: Initial Charging Current less than 0.21A Voltage 14.4-15.0V77°F(25°C) Standby: Voltage 13.5-13.8V77°F(25°C)	

### 放电特性 Discharge Characteristics(0°C/32°F,40°C/104°F)

