


### Specifications 规格

Nominal Voltage 额定电压	12V	
Rated Capacity(20 hour rate) 20小时率额定容量	33AH	
尺寸 Dimensions ± 1mm	Length 长	196mm(7.72")
	Width 宽	131mm(5.16")
	Height 高	156mm(6.14")
	Total Height (with terminals) 总高含端子	180mm(7.09")
Weight 重量	Approx.11.9kg (26.18lbs)	
Standard Terminal 标准端子	A3	

### 放电特性 Discharge Characteristics(20°C,68°F)



### Electrical Specifications 电性能

容量 Capacity 77°F(25°C)	20 hour rate (1.65A) 20小时率	33AH
	10 hour rate (3.07A) 10小时率	30.7AH
	5 hour rate (5.62A) 5小时率	28.1AH
	1 hour rate (18.8A) 1小时率	18.8AH
Internal Resistance 内阻	Fully charged battery 充足电 77°F(25°C)	13m Ω
Capacity 温度	104°F(40°C)	102%
Affected by 对容量	77°F(25°C)	100%
Temperature 影响	32°F(0°C)	85%
(20 hour rate) 20小时率	5°F(-15°C)	65%
自放电 Self-Discharge 77°F(25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
Charge 充电 Constant (恒压) Voltage	循环使用: 首次充电电流低于9.90A 电压: 14.4-15.0V77°F(25°C) 浮充使用: 电压13.5-13.8V77°F(25°C) Cycle: Initial Charging Current less than9.90A Voltage14.4-15.0V77°F(25°C) Standby: Voltage13.5-13.8V77°F(25°C)	

### 放电特性 Discharge Characteristics(0°C/32°F,40°C/104°F)

